



SPECIFICATION

Product model	T-003014-3																																																
Product Size (mm)	559*550*2510mm																																																
Product description	<table> <tr> <td>Body material</td><td>Die Casting Aluminum</td></tr> <tr> <td>Optical cover material</td><td>/</td></tr> <tr> <td>Surface finish</td><td>Pure polyester powder coating</td></tr> <tr> <td>Safety</td><td>CLASS I</td></tr> <tr> <td>Protection Grade</td><td>IP54</td></tr> <tr> <td>Impact Strength(IK)</td><td>IK08</td></tr> <tr> <td>UV-Resistant</td><td>F1</td></tr> <tr> <td>Life Span</td><td>50000 Hrs</td></tr> <tr> <td>Net Weight</td><td>/</td></tr> <tr> <td>Rated Power</td><td>39 W</td></tr> <tr> <td>LED Module Rated Power</td><td>0.5W*72</td></tr> <tr> <td>Input Voltage</td><td>100-240V~</td></tr> <tr> <td>Frequency Range</td><td>50/60 Hz</td></tr> <tr> <td>Luminaire luminous efficiency(EFF)</td><td>86 lm/W</td></tr> <tr> <td>Imax(cd)</td><td>826 cd</td></tr> <tr> <td>Luminaire Efficiency(LOR%)</td><td>62</td></tr> <tr> <td>Total Flux</td><td>3300 lm</td></tr> <tr> <td>Beam angle(At 50% of Imax)</td><td>165°</td></tr> <tr> <td>Energy Efficiency Index(EEI)</td><td>3.61</td></tr> <tr> <td>Colour rendering index(Ra)</td><td>≥80</td></tr> <tr> <td>Colour Temperature(CCT)</td><td>3000K</td></tr> <tr> <td>SCDM</td><td>≤5</td></tr> <tr> <td>Surge transient protection</td><td>L/N:2KV</td></tr> <tr> <td>Working temperature</td><td>-30°C ~ +45°C</td></tr> </table>	Body material	Die Casting Aluminum	Optical cover material	/	Surface finish	Pure polyester powder coating	Safety	CLASS I	Protection Grade	IP54	Impact Strength(IK)	IK08	UV-Resistant	F1	Life Span	50000 Hrs	Net Weight	/	Rated Power	39 W	LED Module Rated Power	0.5W*72	Input Voltage	100-240V~	Frequency Range	50/60 Hz	Luminaire luminous efficiency(EFF)	86 lm/W	Imax(cd)	826 cd	Luminaire Efficiency(LOR%)	62	Total Flux	3300 lm	Beam angle(At 50% of Imax)	165°	Energy Efficiency Index(EEI)	3.61	Colour rendering index(Ra)	≥80	Colour Temperature(CCT)	3000K	SCDM	≤5	Surge transient protection	L/N:2KV	Working temperature	-30°C ~ +45°C
Body material	Die Casting Aluminum																																																
Optical cover material	/																																																
Surface finish	Pure polyester powder coating																																																
Safety	CLASS I																																																
Protection Grade	IP54																																																
Impact Strength(IK)	IK08																																																
UV-Resistant	F1																																																
Life Span	50000 Hrs																																																
Net Weight	/																																																
Rated Power	39 W																																																
LED Module Rated Power	0.5W*72																																																
Input Voltage	100-240V~																																																
Frequency Range	50/60 Hz																																																
Luminaire luminous efficiency(EFF)	86 lm/W																																																
Imax(cd)	826 cd																																																
Luminaire Efficiency(LOR%)	62																																																
Total Flux	3300 lm																																																
Beam angle(At 50% of Imax)	165°																																																
Energy Efficiency Index(EEI)	3.61																																																
Colour rendering index(Ra)	≥80																																																
Colour Temperature(CCT)	3000K																																																
SCDM	≤5																																																
Surge transient protection	L/N:2KV																																																
Working temperature	-30°C ~ +45°C																																																
LED Chip	<table> <tr> <td>LED Brand</td><td>OSRAM</td></tr> <tr> <td>LED Model No.</td><td>2835</td></tr> <tr> <td>LED Nominal Flux(lm)</td><td>70 lm</td></tr> <tr> <td>LED Quantity</td><td>72</td></tr> </table>	LED Brand	OSRAM	LED Model No.	2835	LED Nominal Flux(lm)	70 lm	LED Quantity	72																																								
LED Brand	OSRAM																																																
LED Model No.	2835																																																
LED Nominal Flux(lm)	70 lm																																																
LED Quantity	72																																																
Driver	<table> <tr> <td>STOCK NUMBER</td><td>L-QD-PA136</td></tr> <tr> <td>Driver Brand</td><td>YUNDA</td></tr> <tr> <td>Driver Output</td><td>27-40VDC</td></tr> <tr> <td>Driver Efficiency</td><td>≥81%</td></tr> <tr> <td>Power Factor</td><td>≥0.85</td></tr> <tr> <td>THD</td><td>≤10%</td></tr> <tr> <td>Ripple current</td><td>≤15%</td></tr> </table>	STOCK NUMBER	L-QD-PA136	Driver Brand	YUNDA	Driver Output	27-40VDC	Driver Efficiency	≥81%	Power Factor	≥0.85	THD	≤10%	Ripple current	≤15%																																		
STOCK NUMBER	L-QD-PA136																																																
Driver Brand	YUNDA																																																
Driver Output	27-40VDC																																																
Driver Efficiency	≥81%																																																
Power Factor	≥0.85																																																
THD	≤10%																																																
Ripple current	≤15%																																																
Certification	CE, CCC, CB, SAA, BIS																																																

