



SPECIFICATION

Product model	T-005017-36W	
Product Size (mm)	Ø420*3390mm	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Pure polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	IK08
	UV-Resistant	F1
	Net Weight	6.00 Kg
	Rated Power	36W
	LED Module Rated Power	1W*36
	Input Voltage	220-240V ~
	Frequency Range	50/60 Hz
	Luminaire luminous efficiency(EFF)	73 lm/W
	Imax(cd)	1508 cd
	Luminaire Efficiency(LOR%)	64
	Total Flux	2800 lm
	Beam angle(At 50% of Imax)	100°
	Energy Efficiency Index(EEI)	0.20
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000K
	SDCM	≤5
	Surge transient protection	L/N:1KV
	Working temperature	-30°C ~ +45°C
LED Chip	LED Brand	OSRAM
	LED Model No.	3030
	LED Nominal Flux(lm)	120 lm
	LED Quantity	36 PCS
	Life Span	50000 Hrs
Driver	STOCK NUMBER	L-QD-PA216
	Driver Brand	HEP
	Driver Output	30-42VDC
	Driver Efficiency	≥85%
	Power Factor	≥0.92
	THD	≥10%
	Ripple current	≤10%
Certification	CE, CCC, CB, SAA, BIS	

