



SPECIFICATION

Product model	P-046102-200	
Product Size (mm)	Φ145*2000mm	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Pure polyester powder coating
	Safety	CLASS I
	Protection Grade	IP54
	Impact Strength(IK)	IK06
	UV-Resistant	F1
	Net Weight	/
	Rated Power	30 W
	LED Module Rated Power	30W*1
	Input Voltage	100-240V~
	Frequency Range	50/60 Hz
	Luminaire luminous efficiency(EFF)	82 lm/W
	Imax(cd)	2443 cd
	Luminaire Efficiency(LOR%)	66
	Total Flux	2400 lm
	Beam angle(At 50% of Imax)	85°
	Energy Efficiency Index(EEI)	0.19
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000K
	SCDM	≤5
	Surge transient protection	L/N:1.5KV
	Working temperature	-30°C ~ +45°C
LED Chip	LED Brand	Lumileds
	LED Model No.	L05
	LED Nominal Flux(lm)	3600 lm
	LED Quantity	1
	Life Span	50000 Hrs
Driver	STOCK NUMBER	L-QD-PA151
	Driver Brand	YUNDA
	Driver Output	27-40VDC
	Driver Efficiency	≥82%
	Power Factor	≥0.9
	THD	≤10%
	Ripple current	≤15%
Certification	CE, CCC, CB, SAA, BIS	

