



SPECIFICATION

Product model	P-103235-30																																														
Product Size (mm)	120*300																																														
Product description	<table> <tr> <td>Body material</td><td>Die Casting Aluminum</td></tr> <tr> <td>Optical cover material</td><td>/</td></tr> <tr> <td>Surface finish</td><td>Polyester powder coating</td></tr> <tr> <td>Safety</td><td>CLASS I</td></tr> <tr> <td>Protection Grade</td><td>IP65</td></tr> <tr> <td>Impact Strength(IK)</td><td>IK10</td></tr> <tr> <td>UV-Resistant</td><td>F1</td></tr> <tr> <td>Net Weight</td><td>1.21Kg</td></tr> <tr> <td>Rated Power</td><td>8 W</td></tr> <tr> <td>LED Module Rated Power</td><td>0.33W*24</td></tr> <tr> <td>Input Voltage</td><td>100-240V ~</td></tr> <tr> <td>Frequency Range</td><td>50/60Hz</td></tr> <tr> <td>Luminaire luminous efficiency(EFF)</td><td>63 lm/W</td></tr> <tr> <td>Imax(cd)</td><td>166 cd</td></tr> <tr> <td>Luminaire Efficiency(LOR%)</td><td>44</td></tr> <tr> <td>Total Flux</td><td>590 lm</td></tr> <tr> <td>Beam angle(At 50% of Imax)</td><td>180°</td></tr> <tr> <td>Energy Efficiency Index(EEI)</td><td>0.16</td></tr> <tr> <td>Colour rendering index(Ra)</td><td>≥80</td></tr> <tr> <td>Colour Temperature(CCT)</td><td>3000 K</td></tr> <tr> <td>SCDM</td><td>≤5</td></tr> <tr> <td>Surge transient protection</td><td>L/N:2KV</td></tr> <tr> <td>Working temperature</td><td>-30°C ~ +45°C</td></tr> </table>	Body material	Die Casting Aluminum	Optical cover material	/	Surface finish	Polyester powder coating	Safety	CLASS I	Protection Grade	IP65	Impact Strength(IK)	IK10	UV-Resistant	F1	Net Weight	1.21Kg	Rated Power	8 W	LED Module Rated Power	0.33W*24	Input Voltage	100-240V ~	Frequency Range	50/60Hz	Luminaire luminous efficiency(EFF)	63 lm/W	Imax(cd)	166 cd	Luminaire Efficiency(LOR%)	44	Total Flux	590 lm	Beam angle(At 50% of Imax)	180°	Energy Efficiency Index(EEI)	0.16	Colour rendering index(Ra)	≥80	Colour Temperature(CCT)	3000 K	SCDM	≤5	Surge transient protection	L/N:2KV	Working temperature	-30°C ~ +45°C
Body material	Die Casting Aluminum																																														
Optical cover material	/																																														
Surface finish	Polyester powder coating																																														
Safety	CLASS I																																														
Protection Grade	IP65																																														
Impact Strength(IK)	IK10																																														
UV-Resistant	F1																																														
Net Weight	1.21Kg																																														
Rated Power	8 W																																														
LED Module Rated Power	0.33W*24																																														
Input Voltage	100-240V ~																																														
Frequency Range	50/60Hz																																														
Luminaire luminous efficiency(EFF)	63 lm/W																																														
Imax(cd)	166 cd																																														
Luminaire Efficiency(LOR%)	44																																														
Total Flux	590 lm																																														
Beam angle(At 50% of Imax)	180°																																														
Energy Efficiency Index(EEI)	0.16																																														
Colour rendering index(Ra)	≥80																																														
Colour Temperature(CCT)	3000 K																																														
SCDM	≤5																																														
Surge transient protection	L/N:2KV																																														
Working temperature	-30°C ~ +45°C																																														
LED Chip	<table> <tr> <td>LED Brand</td><td>OSRAM</td></tr> <tr> <td>LED Model No.</td><td>2835</td></tr> <tr> <td>LED Nominal Flux(lm)</td><td>50 lm</td></tr> <tr> <td>LED Quantity</td><td>24 PCS</td></tr> <tr> <td>Life Span</td><td>50000 Hrs</td></tr> </table>	LED Brand	OSRAM	LED Model No.	2835	LED Nominal Flux(lm)	50 lm	LED Quantity	24 PCS	Life Span	50000 Hrs																																				
LED Brand	OSRAM																																														
LED Model No.	2835																																														
LED Nominal Flux(lm)	50 lm																																														
LED Quantity	24 PCS																																														
Life Span	50000 Hrs																																														
Driver	<table> <tr> <td>STOCK NUMBER</td><td>L-QD-PA137</td></tr> <tr> <td>Driver Brand</td><td>YUNDA</td></tr> <tr> <td>Driver Output</td><td>27-40VDC</td></tr> <tr> <td>Driver Efficiency</td><td>≥81%</td></tr> <tr> <td>Power Factor</td><td>≥0.9</td></tr> <tr> <td>THD</td><td>≤16%</td></tr> <tr> <td>Ripple current</td><td>≤20%</td></tr> </table>	STOCK NUMBER	L-QD-PA137	Driver Brand	YUNDA	Driver Output	27-40VDC	Driver Efficiency	≥81%	Power Factor	≥0.9	THD	≤16%	Ripple current	≤20%																																
STOCK NUMBER	L-QD-PA137																																														
Driver Brand	YUNDA																																														
Driver Output	27-40VDC																																														
Driver Efficiency	≥81%																																														
Power Factor	≥0.9																																														
THD	≤16%																																														
Ripple current	≤20%																																														
Certification	CE, CCC, CB, SAA, BIS																																														

