



SPECIFICATION

Product model	P-003338-75	
Product Size (mm)	124*100*750	
Product description	Body material	Die Casting Aluminum
	Optical cover material	/
	Surface finish	Pure polyester powder coating
	Safety	CLASS I
	Protection Grade	IP65
	Impact Strength(IK)	IK08
	UV-Resistant	F1
	Life Span	50000 Hrs
	Net Weight	2.20
	Rated Power	9 W
	LED Module Rated Power	8W*1
	Input Voltage	100-240V~
	Frequency Range	50/60Hz
	Luminaire luminous efficiency(EFF)	55 lm/W
	Imax(cd)	388 cd
	Luminaire Efficiency(LOR%)	61
	Total Flux	490 lm
	Beam angle(At 50% of Imax)	80°
	Energy Efficiency Index(EEI)	0.21
	Colour rendering index(Ra)	≥80
	Colour Temperature(CCT)	3000 K
	SDCM	≤5
	Surge transient protection	L/N:2KV
	Working temperature	-30°C ~ +45°C
LED Chip	LED Brand	CREE
	LED Model No.	1304
	LED Nominal Flux(lm)	800 lm
	LED Quantity	1 PCS
Driver	STOCK NUMBER	L-QD-PA137
	Driver Brand	YUNDA
	Driver Output	27-40VDC
	Driver Efficiency	≥81%
	Power Factor	≥0.9
	THD	≤16%
	Ripple current	≤20%
Certification	CE, CCC, CB, SAA, BIS	

